# **SAFETY DATA SHEET**

GC68112

### Section 1. Identification

Product name	: Geocel® 8125® 100% Silicone High Performance Acetoxy Cure Sealant White
Product code	: GC68112
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Geocel Products Group A Business Unit of the Sherwin-Williams Company 101 W. Prospect Avenue Cleveland, Ohio 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company Product Information Telephone Number	<ul> <li>US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year</li> <li>US / Canada: (800) 348-7615 Mexico: Not Available</li> </ul>
Regulatory Information Telephone Number	: US / Canada: (216) 566-2902 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

Classification of the substance or mixture	<ul> <li>SKIN CORROSION/IRRITATION - Category 1</li> <li>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1</li> <li>CARCINOGENICITY - Category 2</li> <li>TOXIC TO REPRODUCTION - Category 2</li> </ul>
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 5% (oral), 12.2% (dermal), 12.2% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: Causes severe skin burns and eye damage. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022	Version	: 10.01
GC68112	Geocel® 8125® 100% Silie White	cone High Perform	nance Acetoxy Cure Sealant		SHW-85-	NA-GHS-CA

1/14

### Section 2. Hazards identification

Hazards not otherwise classified	: None known.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Supplemental label elements	WARNING: This product contains a chemical known to the State of California to cause cancer.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Storage	: Store locked up.
	person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Response	<ul> <li>protection. Wash thoroughly after handling.</li> <li>IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove</li> </ul>
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Precautionary statements	

### Section 3. Composition/information on ingredients

: Not available.

#### CAS number/other identifiers

Other means of

identification

Ingredient name	% by weight	CAS number
Amorphous Silica	10	7631-86-9
Middle Petroleum Distillates	5	64742-46-7
Ethyl Triacetoxysilane	3.65	17689-77-9
Methyl Triacetoxysilane	3.5	4253-34-3
Acetic Acid	2.85	64-19-7
Titanium Dioxide	1	13463-67-7
Octamethylcyclotetrasiloxane	0.5	556-67-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022
GC68112	Geocel® 8125® 100% Silio White	cone High Perform	ance Acetoxy Cure Sealant	

### Section 4. First aid measures

Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/eff	
Potential acute health effects	-
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	o <u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain

	redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following:

watering

# ngestion : Adverse symptoms may include the following stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022	Version	: 10.01	3/14
GC68112	Geocel® 8125® 100% Silic White	cone High Perform	ance Acetoxy Cure Sealant		SHW-85-	NA-GHS-CA	

### Section 4. First aid measures

Specific treatments

: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Section 6. Accidental release measures

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits (OSHA United States)** 

Ingredient name	CAS #	Exposure limits
Amorphous Silica	NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS] TWA: 6 mg/m <sup>3</sup> 10 hours.	
Middle Petroleum Distillates       64742-46-7       NIOSH REL (United States, 10/20 MIST MINERAL]         TWA: 5 mg/m³ 10 hours. Form: N       STEL: 10 mg/m³ 15 minutes. Form: N		
Ethyl Triacetoxysilane	17689-77-9	None.
Methyl Triacetoxysilane	4253-34-3	None.
Acetic Acid	ACGIH TLV (United States, 1/2022). TWA: 10 ppm 8 hours. TWA: 25 mg/m <sup>3</sup> 8 hours. STEL: 15 ppm 15 minutes. STEL: 37 mg/m <sup>3</sup> 15 minutes. NIOSH REL (United States, 10/2020). TWA: 10 ppm 10 hours. TWA: 25 mg/m <sup>3</sup> 10 hours. STEL: 15 ppm 15 minutes.	
Date of issue/Date of revision : 6/	1/2023 Date of previous issue	: 11/26/2022 Version : 10.01 5/14
GC68112 Geocel® 8125® 100% Silicone White	ligh Performance Acetoxy Cure Sealant	SHW-85-NA-GHS-CA

## Section 8. Exposure controls/personal protection

		STEL: 37 mg/m <sup>3</sup> 15 minutes. OSHA PEL (United States, 5/2018).
		TWA: 10 ppm 8 hours.
		TWA: 25 mg/m³ 8 hours.
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018).
		TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
		ACGIH TLV (United States, 1/2022).
		TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable
		fraction, finescale particles
Octamethylcyclotetrasiloxane	556-67-2	OARS WEEL (United States, 4/2022).
Columentyloyolololanoxano	000 01 2	,
		TWA: 10 ppm 8 hours.

#### **Occupational exposure limits (Canada)**

Ingredient name	CAS #	Exposure limits
Middle Petroleum Distillates	64742-46-7	CA Alberta Provincial (Canada, 6/2018). [Oil mist, mineral] 8 hrs OEL: 5 mg/m <sup>3</sup> 8 hours. Form: Mist 15 min OEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist
Acetic acid	64-19-7	<ul> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>8 hrs OEL: 10 ppm 8 hours.</li> <li>8 hrs OEL: 25 mg/m<sup>3</sup> 8 hours.</li> <li>15 min OEL: 37 mg/m<sup>3</sup> 15 minutes.</li> <li>15 min OEL: 15 ppm 15 minutes.</li> <li>CA British Columbia Provincial (Canada, 6/2022).</li> <li>TWA: 10 ppm 8 hours.</li> <li>STEL: 15 ppm 15 minutes.</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>TWA: 10 ppm 8 hours.</li> <li>STEL: 15 ppm 15 minutes.</li> <li>CA Quebec Provincial (Canada, 6/2022).</li> <li>TWAEV: 10 ppm 8 hours.</li> <li>STEL: 15 ppm 15 minutes.</li> <li>CA Quebec Provincial (Canada, 6/2022).</li> <li>TWAEV: 10 ppm 8 hours.</li> <li>STEV: 15 ppm 15 minutes.</li> <li>STEV: 37 mg/m<sup>3</sup> 15 minutes.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 15 ppm 15 minutes.</li> <li>TWA: 10 ppm 8 hours.</li> </ul>
Octamethylcyclotetrasiloxane	556-67-2	OARS WEEL (United States, 4/2022). TWA: 10 ppm 8 hours.

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
Middle Petroleum Distillates Acetic Acid	64742-46-7NOM-010-STPS-2014 (Mexico, 4/201 [Highly refined mineral oils, mist, with exception of cutting fluids] TWA: 5 mg/m³ 8 hours. Form: mist 	
		TWA: 10 ppm 8 hours. STEL: 15 ppm 15 minutes.

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022	Version	: 10.01	6/14
GC68112	Geocel® 8125® 100% Silio White	cone High Perform	nance Acetoxy Cure Sealant		SHW-85-	NA-GHS-CA	

### Section 8. Exposure controls/personal protection

Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>res</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: Not applicable.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 117°C (242.6°F)
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.97 (butyl acetate = 1)
Flammability	: Not available.

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022	Version :	: 10.01	7/14
GC68112	Geocel® 8125® 100% Silic White	one High Perform	ance Acetoxy Cure Sealant		SHW-85-N	IA-GHS-CA	

### Section 9. Physical and chemical properties

Lower and upper explosion limit/flammability limit	: Lower: 5.4% Upper: 19.3%
Vapor pressure	: 1.5 kPa (11 mm Hg)
Relative vapor density	: 2.07 [Air = 1]
Relative density	: 1.06
Solubility(ies)	:
Not available.	
Partition coefficient: n- octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight	: Not applicable.
Aerosol product	
Heat of combustion	: 5.139 kJ/g

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result			
Methyl Triacetoxysilane	LD50 Oral			
Acetic Acid	LC50 Inhalatio			
	I D50 Dermal			

Product/ingredient name	Result	Species	Dose	Exposure
Methyl Triacetoxysilane	LD50 Oral	Rat	2060 mg/kg	-
Acetic Acid	LC50 Inhalation Vapor	Rat	11000 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	1060 mg/kg	-
	LD50 Oral	Rat	3310 mg/kg	-
Octamethylcyclotetrasiloxane	LC50 Inhalation Vapor	Rat	36 g/m³	4 hours
	LD50 Dermal	Rat	1770 mg/kg	-
	LD50 Oral	Rat	1540 mg/kg	-

#### Irritation/Corrosion

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022	Version	: 10.01	8/14
GC68112	Geocel® 8125® 100% Silic White	cone High Perform	ance Acetoxy Cure Sealant		SHW-85-	NA-GHS-CA	

### Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Amorphous Silica	Eyes - Mild irritant	Rabbit	-	24 hours 25 mg	-
Acetic Acid	Eyes - Mild irritant	Rabbit	-	0.5 minutes 5 mg	-
	Skin - Mild irritant	Human	-	24 hours 50 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 50	-
	Skin - Severe irritant	Rabbit	-	525 mg	-
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Octamethylcyclotetrasiloxane	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Amorphous Silica Titanium Dioxide	-	3 2B	-

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Name	Result
Middle Petroleum Distillates	ASPIRATION HAZARD - Category 1

### Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Eye contact	: Causes serious eye damage.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes severe burns.	
Ingestion	: No known significant effects or critical hazards.	

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022	Version :	: 10.01	9/14
GC68112	Geocel® 8125® 100% Silio White	one High Perform	nance Acetoxy Cure Sealant		SHW-85-N	A-GHS-CA	

### Section 11. Toxicological information

Symptoms related to the ph	ysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate eff	ects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

#### Numerical measures of toxicity

Acute t	toxicit	<u>y estimates</u>

Route	ATE value
Oral Dermal	6595.86 mg/kg 32674.04 mg/kg
Inhalation (vapors)	339.07 mg/l

Date of issue/Date	of revision	: 6/11/2023	Date of previous issue	: 11/26/2022	Version	:10.01	10/14
GC68112	Geocel® 8125® 100% Sili White	icone High Perforr	nance Acetoxy Cure Sealant		SHW-85-	NA-GHS-CA	

### Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Amorphous Silica	Acute EC50 2.2 g/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours 🥄
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
Acetic Acid	Acute EC50 73400 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute EC50 65000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 75000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Octamethylcyclotetrasiloxane	Acute LC50 0.204 to 3.483 mg/l Fresh water	Fish - Leuciscus idus ssp. melanotus	96 hours
	Chronic NOEC 7.9 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 4.4 µg/l Fresh water	Fish - Oncorhynchus mykiss - Egg	93 days

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Acetic Acid	-	3.16	low 💙
Octamethylcyclotetrasiloxane	-	13400	high

#### <u>Mobility in soil</u>

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

UN proper shipping name     -     -     -       -     -     -     ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cetamethyloydolettraslozare)     ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cetamethyloydolettraslozare)     ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cetamethyloydolettraslozare)       Transport hazard class(es)     -     -     9       Packing group     -     -     9       Packing group     -     -     III       Environmental hazards     No.     No.     No.       Additional information     -     -     -       -     -     -     This product is not regulated as a dangerous good when transported in sizes of ≤5 L or s5 kg, provided the packagings meet the general provisions of s0 2.4.1, 5.0.2.4.1.1 and 4.1.1.8		Mexico Classification	TDG Classification	DOT Classification	
shipping name       HAZARDOUS       HAZARDOUS         substance       LiQUID, N.O.S.       LiQUID         Transport       -       -       9         hazard class(es)       -       -       9         Packing group       -       -       III       III         Environmental hazards       No.       No.       Yes.       Yes.         Additional information       -       -       -       This product is good when transported in sizes of 55 L or transported in sis sizes of 55 L or transported in sis sizes of 55 L o	d. UN3082 UN3082	Not regulated.	Not regulated.	Not regulated.	UN number
hazard class(es)IIIIIIPacking groupIIIIIIEnvironmental hazardsNo.No.No.Yes.Yes.Additional informationThis product is not regulated as a dangerous good when transported in is zes of 45 L or \$5 kg, provided the packagings meet the general provisions of \$0.2.6.1.1 andThis provisi 4.1.1.8	HAZARDOUS SUBSTANCE, LIQUID, N.O.S. HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-	-	UN proper shipping name
Environmental hazards     No.     No.     No.     Yes.     Yes.       Additional information     -     -     -     This product is not regulated as a dangerous good when when t transported in sizes of ≤5 L or ≤5 kg, sizes of ≤5 L or ≤5 kg, sizes of ≤5 L or ≤5 kg, meet the general provisions of 4.1.1.1 5.0.2.4.1, and 4.7 5.0.2.6.1.1 and 4.1.1.8		-	-	-	Transport hazard class(es)
hazardsThis product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings provisions of 5.0.2.6.1.1 andThis product is regulat danger good when the packagings meet th s.0.2.6.1.1 andThis product is regulat danger the packagings the packagings		-	-	-	Packing group
informationnot regulated as a dangerous good when transported in in sizes sizes of ≤5 L or ≤5 kg, provided the packagings provisions of 4.1.1.1 5.0.2.4.1, and 4.1.1.8not regulated as danger udanger good when transported in in sizes sizes of ≤5 L or sizes of ≤5 kg, 	Yes. Yes.	No.	No.	No.	
	not regulated as a dangerous good when transported in sizes of $\leq 5$ L or $\leq 5$ kg, provided the packagings meet the general provisions of $5.0.2.6.1.1$ and $5.0.2.8.$ regulated as a dangerous good when transported in sizes of $\leq 5$ L or $\leq 5$ kg, provided the packagings meet the general provisions of $4.1.1.4$ to $4.1.1.8$ .Emergency schedulesF-A, S	-	-	-	

consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Date of issue/Date of revision		: 6/11/2023	Date of previous issue	: 11/26/2022	Version	:10.01	12/14
	GC68112 Geocel® 8125® 100% Silicone High Performance Acetoxy Cure Sealant White		nance Acetoxy Cure Sealant		SHW-85-	NA-GHS-CA	

### Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.

### Section 15. Regulatory information

International regulations	
International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 CARCINOGENICITY - Category 2	Calculation method Calculation method Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method

**History** 

<u>Inotory</u>		
Date of printing	1	6/11/2023
Date of issue/Date of revision	1	6/11/2023
Date of previous issue	1	11/26/2022
Version	1	10.01

### Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.