

SECTION 1: Identification

1.1. Identification

Product name : Diesel Treat
Product code : 103060, 103061, 103062, 103064, 103065, 103066, 103068, 103070, 103089

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Diesel fuel additive

1.3. Details of the supplier of the safety data sheet

Manufacturer

R.B. Howes & Co., Inc.
3511 North Ohio Street
Wichita, 67219 - USA
T 401-294-5500, 1-800 GET HOWES (438-4693)

Manufacturer

R.B. Howes & Co., Inc.
35 Regan Road
Brampton, L7A 1B2 - Canada
T 401-294-5500, 1-800 GET HOWES (438-4693)

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300 / 703-527-3887

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Liq. 4
Carc. 2
Repr. 2
Asp. Tox. 1

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS08

Signal word (GHS) : Danger
Hazard statements (GHS) : Combustible liquid. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways
Precautionary statements (GHS) : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a doctor. Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

3.2. Mixtures

| Name | Product identifier | % |
|---|----------------------|-----------|
| Distillates, petroleum, hydrotreated light naphthenic | (CAS-No.) 64742-53-6 | 30 - 60 |
| Distillates, petroleum, hydrotreated heavy naphthenic | (CAS-No.) 64742-52-5 | 30 - 60 |
| Stoddard solvent | (CAS No) 8052-41-3 | 10 - 30 |
| Petroleum distillates, hydrotreated light | (CAS No) 64742-47-8 | 10 - 30 |
| Benzene, 1,2,4-trimethyl- | (CAS No) 95-63-6 | 1 - 5 |
| Solvent naphtha, petroleum, light aromatic | (CAS-No.) 64742-95-6 | 1 - 5 |
| Nonane | (CAS No) 111-84-2 | 0.5 - 1.5 |
| Naphthalene | (CAS-No.) 91-20-3 | 0.1 - 1 |
| Xylenes (o-, m-, p- isomers) | (CAS-No.) 1330-20-7 | 0.1 - 1 |
| Ethylbenzene | (CAS-No.) 100-41-4 | 0.1 - 1 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Carbon dioxide. Water fog.
- Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon.
- Reactivity : No dangerous reaction known under conditions of normal use.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Cool down the containers exposed to heat with a water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Spilled material may present a slipping hazard. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5) | | |
|--|--|--------------------------|
| Not applicable | | |
| Distillates, petroleum, hydrotreated light naphthenic (64742-53-6) | | |
| Not applicable | | |
| Stoddard solvent (8052-41-3) | | |
| ACGIH | ACGIH TWA (ppm) | 100 ppm |
| ACGIH | Remark (ACGIH) | Eye, skin, & kidney dam; |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 2900 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 500 ppm |
| IDLH | US IDLH (mg/m ³) | 20000 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 350 mg/m ³ |
| NIOSH | NIOSH REL (ceiling) (mg/m ³) | 1800 mg/m ³ |
| Petroleum distillates, hydrotreated light (64742-47-8) | | |
| Not applicable | | |
| Benzene, 1,2,4-trimethyl- (95-63-6) | | |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 125 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 25 ppm |
| Nonane (111-84-2) | | |
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1050 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 200 ppm |
| Naphthalene (91-20-3) | | |
| ACGIH | ACGIH TWA (ppm) | 10 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 50 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 10 ppm |
| IDLH | US IDLH (ppm) | 250 ppm |

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Naphthalene (91-20-3) | | |
|--|---------------------------------------|-----------------------------------|
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 50 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 10 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 75 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 15 ppm |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | | |
| ACGIH | ACGIH TWA (ppm) | 100 ppm |
| ACGIH | ACGIH STEL (ppm) | 150 ppm |
| ACGIH | Remark (ACGIH) | URT & eye irr; CNS impair |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| Ethylbenzene (100-41-4) | | |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| ACGIH | Remark (ACGIH) | URT irr; kidney dam (nephropathy) |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| IDLH | US IDLH (ppm) | 800 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 435 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 545 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 125 ppm |
| Solvent naphtha, petroleum, light aromatic (64742-95-6) | | |
| Not applicable | | |

8.2. Exposure controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Hand protection | : Wear suitable gloves. |
| Eye protection | : Safety glasses or goggles are recommended when using product. |
| Skin and body protection | : Wear suitable protective clothing. |
| Respiratory protection | : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Environmental exposure controls | : Avoid release to the environment. |
| Other information | : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|-------------------------------------|
| Physical state | : Liquid |
| Appearance | : No data available. |
| Colour | : Light amber |
| Odour | : Distinctive |
| Odour threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : 164 °C (327 °F) |
| Flash point | : ≥ 65.5 °C (≥ 150 °F) [Closed cup] |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Flammability (solid, gas) | : Combustible liquid |

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| | |
|---------------------------------------|-----------------------------|
| Vapour pressure | : < 0.1 mm Hg |
| Relative vapour density at 20 °C | : > 1 (air = 1) |
| Relative density | : < 0.9 (water = 1) |
| Solubility | : Insoluble |
| Partition coefficient n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : 3.89 cSt @ 40 °C (104 °F) |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|-------------------|
| Acute toxicity (oral) | : Not classified. |
| Acute toxicity (dermal) | : Not classified. |
| Acute toxicity (inhalation) | : Not classified. |

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

| | |
|--------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

| | |
|---------------------|---|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | 2180 mg/m ³ (Exposure time: 4 h) |

Petroleum distillates, hydrotreated light (64742-47-8)

| | |
|---------------------|---------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | > 5.2 mg/l/4h |

Benzene, 1,2,4-trimethyl- (95-63-6)

| | |
|---------------------|--|
| LD50 oral rat | 3280 mg/kg |
| LD50 dermal rabbit | > 3160 mg/kg |
| LC50 inhalation rat | 18 g/m ³ (Exposure time: 4 h) |

Nonane (111-84-2)

| | |
|---------------------|-------------|
| LC50 inhalation rat | 3200 ppm/4h |
|---------------------|-------------|

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Naphthalene (91-20-3) | |
|------------------------------|--|
| LD50 oral rat | 1110 mg/kg |
| LD50 dermal rabbit | 1120 mg/kg |
| LC50 inhalation rat | > 340 mg/m ³ (Exposure time: 1 h) |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|---------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | > 4350 mg/kg |
| LD50 dermal | 1700 mg/kg |
| LC50 inhalation rat | 29.08 mg/l/4h |
| LC50 inhalation rat (Vapours - mg/l/4h) | 27.57 mg/l/4h |

| Ethylbenzene (100-41-4) | |
|--------------------------------|--------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | 15400 mg/kg |
| LC50 inhalation rat | 17.4 mg/l/4h |

| Solvent naphtha, petroleum, light aromatic (64742-95-6) | |
|--|--------------|
| LD50 oral rat | 8400 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | 3400 ppm/4h |

| | |
|-----------------------------------|--------------------------------|
| Skin corrosion/irritation | : Not classified. |
| Serious eye damage/irritation | : Not classified. |
| Respiratory or skin sensitisation | : Not classified. |
| Germ cell mutagenicity | : Not classified. |
| Carcinogenicity | : Suspected of causing cancer. |

| Naphthalene (91-20-3) | |
|--|--|
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen |
| In OSHA Hazard Communication Carcinogen list | Yes |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|----------------------|
| IARC group | 3 - Not classifiable |

| Ethylbenzene (100-41-4) | |
|--|--------------------------------------|
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 1 - Evidence of Carcinogenicity |
| In OSHA Hazard Communication Carcinogen list | Yes |

| | |
|-----------------------|--|
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| STOT-single exposure | : Not classified. |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

| Solvent naphtha, petroleum, light aromatic (64742-95-6) | |
|--|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

| | |
|------------------------|---|
| STOT-repeated exposure | : Not classified. |
| Aspiration hazard | : May be fatal if swallowed and enters airways. |

| Diesel Treat | |
|---|--|
| Viscosity, kinematic (calculated value) | < 20.5 mm ² /s @ 40 °C (104 °F) |

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. |
| Symptoms/effects after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. |
| Symptoms/effects after eye contact | : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. |

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

LC50 fish 1 > 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

EC50 Daphnia 1 > 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

LC50 fish 1 > 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

EC50 Daphnia 1 > 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Petroleum distillates, hydrotreated light (64742-47-8)

LC50 fish 1 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

LC50 fish 2 2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Benzene, 1,2,4-trimethyl- (95-63-6)

LC50 fish 1 7.19 - 8.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

EC50 Daphnia 1 6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Naphthalene (91-20-3)

LC50 fish 1 5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

EC50 Daphnia 1 2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)

LC50 fish 2 1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

EC50 Daphnia 2 1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])

Xylenes (o-, m-, p- isomers) (1330-20-7)

LC50 fish 1 13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

EC50 Daphnia 1 3.82 mg/l (Exposure time: 48 h - Species: water flea)

LC50 fish 2 2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

EC50 Daphnia 2 0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

Ethylbenzene (100-41-4)

LC50 fish 1 11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

EC50 Daphnia 1 1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)

LC50 fish 2 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

NOEC chronic crustacea 0.956 mg/l

Solvent naphtha, petroleum, light aromatic (64742-95-6)

LC50 fish 1 9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

EC50 Daphnia 1 6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

Diesel Treat

Persistence and degradability Not established.

12.3. Bioaccumulative potential

Diesel Treat

Bioaccumulative potential Not established.

Petroleum distillates, hydrotreated light (64742-47-8)

BCF fish 1 61 - 159

Benzene, 1,2,4-trimethyl- (95-63-6)

Partition coefficient n-octanol/water 3.63

Naphthalene (91-20-3)

BCF fish 1 30 - 430

Partition coefficient n-octanol/water 3.6

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|-------------|
| BCF fish 1 | 0.6 - 15 |
| Partition coefficient n-octanol/water | 2.77 - 3.15 |

| Ethylbenzene (100-41-4) | |
|---------------------------------------|-----|
| BCF fish 1 | 15 |
| Partition coefficient n-octanol/water | 3.2 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
UN-No.(DOT) : UN1268
Proper Shipping Name (DOT) : Petroleum distillates, n.o.s.
Class (DOT) : Combustible liquid
Packing group (DOT) : III

Transportation of Dangerous Goods (TDG)

In accordance with TDG
Not regulated

Transport by sea

This product is currently not packaged to comply with IMDG regulations. It is not intended to be shipped by sea.

Transport by air

This product is currently not packaged to comply with IATA regulations. It is not intended to be shipped by air.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

| Benzene, 1,2,4-trimethyl- (95-63-6) | |
|---|--|
| Subject to reporting requirements of United States SARA Section 313 | |

| Nonane (111-84-2) | |
|--------------------------|--|
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a final TSCA section 4 test rule. |

| Naphthalene (91-20-3) | |
|---|--|
| Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS) | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a final TSCA section 4 test rule. |
| CERCLA RQ | 100 lb |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|--------|
| Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS) | |
| CERCLA RQ | 100 lb |

Diesel Treat

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| | |
|---|---|
| Ethylbenzene (100-41-4) | |
| Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS) | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a final TSCA section 4 test rule. |
| CERCLA RQ | 1000 lb |
| Isopropylbenzene (98-82-8) | |
| Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS) | |
| CERCLA RQ | 5000 lb |
| 2-Ethylhexanol (104-76-7) | |
| EPA TSCA Regulatory Flag | TP - TP - indicates a substance that is the subject of a proposed TSCA section 4 test rule. |

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


| Component | State or local regulations |
|---|--|
| Benzene, 1,2,4-trimethyl-(95-63-6) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Nonane(111-84-2) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Xylenes (o-, m-, p- isomers)(1330-20-7) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Naphthalene(91-20-3) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Ethylbenzene(100-41-4) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Stoddard solvent(8052-41-3) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| Distillates, petroleum, hydrotreated light naphthenic(64742-53-6) | U.S. - Massachusetts - Right To Know List |

SECTION 16: Other information

Revision date : 03/01/2019
 Other information : None.
 Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



NFPA health hazard : 2
 NFPA fire hazard : 2
 NFPA reactivity : 0



SDS HazCom 2012 - WHMIS 2015 (NexReg) - Section 15

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.