

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

1. Identification

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Two Cycle Engine Oil

Restrictions on use:Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

importer, or other responsible party:

Warren Distribution, Inc.

950 S. 10th St., Suite 300

Omaha, NE 68108-3296

Phone number: +01 (800) 825-1235 +01 (402) 341-9397

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:







GHS Classification: Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2B

Germ Cell Mutagenicity Category 1B

Carcinogenicity Category 1A

Reproductive Toxicity Category 2

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure

Category 1

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category

1

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

3

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category

3

Hazardous to the aquatic environment - Acute Category 1

Hazardous to the aquatic environment - Chronic Category 1

Signal Word: Danger

Hazard Statements: Causes skin and eye irritation; May cause genetic defects; May cause

cancer.; Suspected of damaging fertility or the unborn child.; Causes damage to organs; Causes damage to organs through prolonged or repeated exposure; Very toxic to aquatic life; Very toxic to aquatic life

with long lasting effects

Precautionary Statements:

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Do not breathe

dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the

environment. Wear protective gloves/protective clothing/eye

protection/face protection.

Response: If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with

water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center/doctor/... If exposed

or concerned: Get medical advice/attention. Get medical

advice/attention if you feel unwell. Specific treatment (see Sections 4 - 8

of Safety Data Sheet). If skin irritation occurs: Get medical

advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulations.

Hazards not otherwise classified: Repeated exposure may cause skin dryness or cracking.

Flammable vapors can accumulate in head space of closed systems.

3. Composition/information on ingredients

| Chemical Name | mical Name Common name and synonyms | | % |
|------------------------|-------------------------------------|------------|---------|
| Petroleum distillates, | No data available | 64742-54-7 | 30 - 60 |

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

| hydrotreated heavy paraffinic | | | |
|-----------------------------------|--------------------|------------|---------|
| Distillates, petroleum, straight- | No data available | 64741-44-2 | 10 - 30 |
| run middle | | | |
| Distillates, petroleum, | No data available | 64742-80-9 | 10 - 30 |
| · · | 140 data available | 04742 00 7 | 10 30 |
| hydrodesulfurized middle | | | |
| Distillates, petroleum, | No data available | 68333-25-5 | 10 - 30 |
| hydrodesulfurized light catalytic | | | |
| cracked | | | |
| Kerosene | No data available | 8008-20-6 | 10 - 30 |
| Residual oils (petroleum), | No data available | 64742-62-7 | 10 - 30 |
| solvent dewaxed | | | |
| Kerosine, petroleum, | No data available | 64742-81-0 | 7 - 13 |
| hydrodesulfurized | | | |
| Light hydrocracked distillate | No data available | 64741-77-1 | 3 - 7 |
| Mineral oil, white | No data available | 8042-47-5 | 1 - 5 |
| Naphthalene | No data available | 91-20-3 | 0.1 - 1 |
| Toluene | No data available | 108-88-3 | 0.1 - 1 |
| Ethylbenzene | No data available | 100-41-4 | 0.1 - 1 |
| Benzene | No data available | 71-43-2 | 0.1 - 1 |
| Biphenyl | No data available | 92-52-4 | 0.1 - 1 |

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

Eye Contact: If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

Skin Contact: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before

reuse.

Ingestion: Seek medical attention immediately or call the Poison control center. Do

not induce vomiting. If patient is fully conscious, give up to two glasses

of water. Provide medical care provider with this SDS.

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

Most important symptoms/effects,

acute and delayed:

Indication of immediate medical attention and special treatment

needed, if necessary:

Causes skin and eye irritation Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

Specific treatment (see Sections 4 - 8 of Safety Data Sheet). If exposed or

concerned: Get medical advice/attention. If exposed: Call a poison center/doctor/... Get medical advice/attention if you feel unwell.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

Material may be ignited only if preheated to temperatures above the

high flash point, for example in a fire.

Hazardous combustion products: Carbon dioxide, Carbon monoxide

Special protective equipment and

precautions for fire-fighters:

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the

surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid release to the environment.

Methods and materials for containment

and cleaning up:

Collect spillage.

7. Handling and storage

Precautions for safe handling:Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood.

Conditions for safe storage, including

any incompatibilities:

Safe storage conditions: Store locked up.

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

| Chemical component | OSHA PEL | ACGIH TLV | ACGIH STEL | IDLH |
|------------------------|--------------------------------------|---|---------------|-------------------|
| Petroleum distillates, | 5 mg/m3 TWA | 5 mg/m3 TWA | 10 mg/m3 STEL | No data available |
| hydrotreated heavy | | | | |
| paraffinic | | | | |
| Kerosene | No PEL | 200 mg/m3 TWA | No STEL | No data available |
| | | (application | | |
| | | restricted to conditions in which | | |
| | | | | |
| | | there are negligible aerosol exposures, | | |
| | | total hydrocarbon | | |
| | | vapor, listed under | | |
| | | Kerosene/Jet fuels) | | |
| Kerosine, petroleum, | No PEL | 200 mg/m3 TWA | No STEL | No data available |
| hydrodesulfurized | | (application | | |
| | | restricted to | | |
| | | conditions in which | | |
| | | there are negligible | | |
| | | aerosol exposures, | | |
| | | total hydrocarbon | | |
| | | vapor, listed under | | |
| N. I.I. | 10 TMA FO | Kerosene/Jet fuels) | N. CTEL | 050 15111 |
| Naphthalene | 10 ppm TWA; 50 | 10 ppm TWA | No STEL | 250 ppm IDLH |
| Taluana | mg/m3 TWA | 20 ppm T\// | No CTEL | FOO name IDIII |
| Toluene | 200 ppm TWA | 20 ppm TWA | No STEL | 500 ppm IDLH |
| Benzene | 10 ppm TWA | 0.5 ppm TWA | 2.5 ppm STEL | 500 ppm IDLH |
| | (applies to industry segments exempt | | | |
| | from the benzene | | | |
| | standard at 29 CFR | | | |
| | 1910.1028); 1 ppm | | | |
| | TWA | | | |
| Ethylbenzene | 100 ppm TWA; 435 | 20 ppm TWA | No STEL | 800 ppm IDLH (10% |

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

| | mg/m3 TWA | | | LEL) |
|----------|----------------|-------------|---------|----------------|
| Biphenyl | 0.2 ppm TWA; 1 | 0.2 ppm TWA | No STEL | 100 mg/m3 IDLH |
| | mg/m3 TWA | | | |

Appropriate engineering controls: Local exhaust ventilation or other engineering controls are normally

required when handling or using this product to avoid overexposure.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Do not breathe dust/fume/gas/mist/vapors/spray.

Respirator Type(s): If airborne concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection. A respiratory protection

program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2

requirements must be followed whenever workplace conditions warrant

a respirator's use.

Eye protection: Wear chemically resistant safety glasses with side shields when handling

this product. Do not wear contact lenses.

Skin protection: Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Gloves: Neoprene, Nitrile

General hygiene conditions: Do not eat, drink or smoke when using this product. Wash hands

thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Blue
Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:No data availableFreezing point:No data availableInitial boiling point and boiling rangeNo data available

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

(°C):

Flash Point (°C): 165

Evaporation Rate: No data available **Flammability (solid, gas):** No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Not established

Lower flammability or explosive

limits:

Not established

Vapor pressure: = 10 - 210 MMHG > 3 MMHG

Vapor density: No data available

Relative density: 0.86

Solubility(ies): Negligible; 0-1%
Partition coefficient: n-octanol/water: No data available
Auto-ignition temperature: No data available
Decomposition Temperature: Not determined

Viscosity: 30.07

10. Stability and reactivity

Reactivity: There are no known reactivity hazards associated with this product.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None expected under standard conditions of storage.

Conditions to avoid (e.g., staticTemperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.

Moisture (will lead to product performance degradation).

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide, carbon dioxide.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

Inhalation, Ingestion, Skin contact, Eye contact

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

and eye contact):

Symptoms related to the physical,

chemical and toxicological

characteristics:

Causes skin and eye irritation Causes damage to organs. Causes damage

to organs through prolonged or repeated exposure.

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion: No hazard in normal industrial use. Estimated to be > 5.0 g/kg.

Skin Contact: Causes skin and eye irritation

Absorption: Estimated to be > 5.0 g/kg; practically non-toxic

Inhalation: No hazard in normal industrial use. Likely to be moderately toxic based

on animal data.

Eye Contact: The material is likely to be moderately irritating to eyes based on animal

data. Can cause moderate irritation, tearing and reddening, but not likely

to permanently injure eye tissue.

Sensitization: Non-hazardous under Respiratory Sensitization category. No data

available to indicate product or components may be a skin sensitizer.

Mutagenicity: Mutagenic affects in humans may occur.

Carcinogenicity: Contains a known human carcinogen.

Reproductive toxicityContains a substance that is a possible reproductive system hazard based

on animal studies at doses that could be encountered in the workplace.

Possible reproductive hazard.

STOT-single exposure: Classification has been based on toxicological information of the

components in Section 3.

STOT-repeated exposure: Classification has been based on toxicological information of the

components in Section 3.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: None known.

Numerical measures of toxicity (such as acute toxicity estimates):

| Chemical Name | Chemical Name LD50 Oral | | LC50 Inhalation | |
|---------------|---------------------------|---------------------------|--------------------------|--|
| Pinhonyl | Oral LD50 Rat > 1900 | Dermal LD50 Rabbit > 2500 | Inhalation LC50 (4h) | |
| Biphenyl | mg/kg | mg/kg | Mouse > 0.275 mg/L | |
| Toluene | Oral LD50 Rat 2600 mg/kg | Dermal LD50 Rabbit 12000 | Inhalation LC50 (4h) Rat | |
| roiderie | Oral LD50 Rat 2000 Hig/kg | mg/kg | 12.5 mg/L | |
| Ethylbenzene | Oral LD50 Rat 3500 mg/kg | Dermal LD50 Rabbit 15400 | Inhalation LC50 (4h) Rat | |

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

| | | mg/kg | 17.4 mg/L |
|----------------------------|----------------------------|---------------------------|----------------------------|
| Benzene | Oral I DEO Dat > 020 mg/kg | Dermal LD50 Rabbit > 8200 | Inhalation LC50 (4h) Rat |
| Бенгене | Oral LD50 Rat > 930 mg/kg | mg/kg | 13050 - 14380 ppm |
| Naphthalene | Oral LD50 Rat 490 mg/kg | Dermal LD50 Rabbit 1120 | Inhalation LC50 (1h) Rat > |
| Napritrialerie | Oral ED30 Kat 470 mg/kg | mg/kg | 340 MG/M3 |
| Mineral oil, white | Oral LD50 Rat > 5000 | | |
| | mg/kg | | |
| Light hydrocracked | Oral LD50 Rat 3200 mg/kg | Dermal LD50 Rabbit > 2000 | Inhalation LC50 (4h) Rat |
| distillate | Oral ED30 Nat 3200 mg/kg | mg/kg | 4.65 mg/L |
| Kerosine, petroleum, | Oral LD50 Rat > 5000 | Dermal LD50 Rabbit > 2000 | Inhalation LC50 (4h) Rat > |
| hydrodesulfurized | mg/kg | mg/kg | 5200 MG/M3 |
| Residual oils (petroleum), | Oral LD50 Rat > 5000 | Dermal LD50 Rabbit > 2000 | Inhalation LC50 (4h) Rat |
| solvent dewaxed | mg/kg | mg/kg | 2.18 mg/L |
| Kerosene | Oral LD50 Rat > 5000 | Dermal LD50 Rabbit > 2000 | Inhalation LC50 (4h) Rat > |
| Keroserie | mg/kg | mg/kg | 5.28 mg/L |
| Distillates, petroleum, | Oral LD50 Rat > 5000 | Dermal LD50 Rabbit > 2000 | Inhalation LC50 (4h) Rat |
| straight-run middle | mg/kg | mg/kg | 1.78 mg/L |
| Distillates, petroleum, | Oral LD50 Rat > 5000 | Dermal LD50 Rabbit > 2000 | Inhalation LC50 (4h) Rat |
| hydrodesulfurized middle | mg/kg | mg/kg | 4.6 mg/L |
| Distillates, petroleum, | | Dermal LD50 Rabbit > 2000 | Inhalation LC50 (4h) Rat |
| hydrodesulfurized light | Oral LD50 Rat 3200 mg/kg | | , , |
| catalytic cracked | | mg/kg | 4.65 mg/L |
| Petroleum distillates, | Oral LD50 Rat > 15000 | Dermal LD50 Rabbit > 5000 | |
| hydrotreated heavy | mg/kg | mg/kg | |
| paraffinic | ilig/kg | ilig/kg | |

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

| Chemical Name | OSHA Carcinogen | IARC Carcinogen | NTP Carcinogen |
|---------------|-----------------|-----------------|----------------|
| Benzene | Υ | Υ | Υ |
| Ethylbenzene | Υ | Υ | N |
| Naphthalene | Υ | Υ | Υ |

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

Ecological Toxicity Data:

| Chemical Name | CAS# | Aquatic EC50 Crustacea | Aquatic ERC50 Algae | Aquatic LC50 Fish |
|--|------------|---|-----------------------------------|--|
| Biphenyl | 92-52-4 | EC50 (48h) Daphnia magna 0.63 - 0.85 mg/L | No data available | LC50 (96h) Rainbow Trout 1.4 - 1.6 mg/L LC50 (96h) Lepomis macrochirus (Bluegill) 4.3 - 5.1 mg/L LC50 (96h) Pimephales promelas (Fathead Minnow) 1.17 - 1.81 mg/L LC50 (96h) Pimephales promelas (Fathead Minnow) 1.65 - 2.29 mg/L |
| Toluene | 108-88-3 | LC50 (48h) Daphnia magna 5.46 - 9.83 mg/L | Aquatic ERC50 (96h) > 433 mg/L | LC50 (96h) 15.22 - 19.05 mg/L |
| Benzene | 71-43-2 | EC50 (48h) Daphnia magna 8.76 - 15.6 mg/L | Aquatic ERC50 (72h) 29 mg/L | LC50 (96h) Rainbow Trout 5.3 mg/L |
| Ethylbenzene | 100-41-4 | EC50 (48h) Daphnia magna 1.8 - 2.4 mg/L | Aquatic ERC50 (72h) 4.6 mg/L | LC50 (96h) Rainbow Trout 11 - 18 mg/L |
| Naphthalene | 91-20-3 | EC50 (48h) Daphnia magna 2.16 mg/L | No data available | LC50 (96h) Rainbow Trout 1.6 mg/L |
| Mineral oil, white | 8042-47-5 | No data available | No data available | LC50 (96h) > 10000 mg/L |
| Light hydrocracked distillate | 64741-77-1 | No data available | No data available | LC50 (96h) BRACHYDANIO RERIO 7.3 mg/L |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | EC50 (48h) 4720 mg/L | No data available | LC50 (96h) 45 mg/L |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | EC50 (48h) Daphnia magna > 1000 mg/L | No data available | LC50 (96h) Rainbow Trout > |

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

| | | | | 5000 mg/L |
|--------------------------|------------|---|-------------------|-------------------|
| Distillates, petroleum, | | | | LC50 (96h) |
| hydrodesulfurized light | 68333-25-5 | No data available | No data available | BRACHYDANIO |
| catalytic cracked | | | | RERIO 7.3 mg/L |
| Distillates, petroleum, | | | | LC50 (96h) |
| hydrodesulfurized middle | 64742-80-9 | No data available | No data available | Pimephales |
| | 04742-00-9 | ino data available | NO data available | promelas (Fathead |
| | | | | Minnow) 35 mg/L |
| Petroleum distillates, | | ECEO (40h) Danhaia | | LC50 (96h) |
| hydrotreated heavy | 64742-54-7 | EC50 (48h) Daphnia magna > 1000 mg/L | No data available | Rainbow Trout > |
| paraffinic | | mayria > 1000 mg/L | | 5000 mg/L |

Persistence and degradability:Biodegrades slowly.

Bioaccumulative potential: Bioconcentration may occur.

Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as

hazardous to the ozone layer):

None known.

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

packaging:

Contaminated packaging:

Dispose of contents and container in accordance with local/regional/national/international regulations.

Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:Not regulated for road transport

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG

UN Proper shipping name: Not applicable Transport hazard class(es): Not applicable

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 **Revision Date: 12-11-2020 Replaces:** 07-14-2020

Packing group, if applicable: Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name: Not applicable Transport hazard class(es): Not applicable Packing group, if applicable: Not applicable

Environmental hazards (e.g., Marine

Yes

pollutant (Yes/No)):

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with

in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the Active US TSCA Inventory or

are exempt.

Regulated Components:

| Chemical Name | CAS# | CERCLA | Sara EHS | Sara 313 | U.S. HAP |
|-------------------------|------------|--------|----------|----------|----------|
| Petroleum distillates, | | | | | |
| hydrotreated heavy | 64742-54-7 | N | N | N | N |
| paraffinic | | | | | |
| Distillates, | | | | | |
| petroleum, straight- | 64741-44-2 | N | N | N | N |
| run middle | | | | | |
| Distillates, | | | | | |
| petroleum, | 68333-25-5 | N | N | N | N |
| hydrodesulfurized | 00333-23-3 | IN | I IV | I N | IV |
| light catalytic cracked | | | | | |
| Distillates, | 64742-80-9 | N | N | N | N |
| petroleum, | 04/42-00-9 | IV | IN | IN | IV |

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

| hydrodesulfurized middle | | | | | |
|--|------------|---|---|---|---|
| Kerosene | 8008-20-6 | N | N | N | N |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | N | N | N | N |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | N | N | N | N |
| Light hydrocracked distillate | 64741-77-1 | N | N | N | N |
| Mineral oil, white | 8042-47-5 | N | N | N | N |
| Naphthalene | 91-20-3 | Υ | N | Υ | Υ |
| Toluene | 108-88-3 | Υ | N | Υ | Υ |
| Benzene | 71-43-2 | Υ | N | Υ | Υ |
| Ethylbenzene | 100-41-4 | Υ | N | Υ | Υ |
| Biphenyl | 92-52-4 | Υ | N | Υ | Υ |

| Chemical Name | CAS# | California Prop 65 - Cancer | California Prop 65 - Dev. Toxicity | California Prop 65 - Reprod fem | California Prop 65 - Reprod male |
|--|------------|--------------------------------|---------------------------------------|------------------------------------|-------------------------------------|
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N |
| Distillates, petroleum, straight- run middle | 64741-44-2 | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | 68333-25-5 | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized middle | 64742-80-9 | N | N | N | N |
| Kerosene | 8008-20-6 | N | N | N | N |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | N | N | N | N |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | N | N | N | N |
| Light hydrocracked | 64741-77-1 | N | N | N | N |

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

| distillate | | | | | |
|--------------------|-----------|---|---|---|---|
| Mineral oil, white | 8042-47-5 | N | N | N | N |
| Naphthalene | 91-20-3 | Υ | N | N | N |
| Toluene | 108-88-3 | N | Υ | N | N |
| Benzene | 71-43-2 | Υ | Υ | N | Υ |
| Ethylbenzene | 100-41-4 | Υ | N | N | N |
| Biphenyl | 92-52-4 | N | N | N | N |

| Chemical Name | CAS# | Massachusetts RTK List | New Jersey RTK List | Pennsylvania RTK List | Rhode Island RTK List | Minnesota Hazardous Substance List |
|--|------------|---------------------------|------------------------|--------------------------|-----------------------------|---|
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N | N |
| Distillates, petroleum, straight- run middle | 64741-44-2 | N | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | 68333-25-5 | N | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized middle | 64742-80-9 | N | N | N | N | N |
| Kerosene | 8008-20-6 | Υ | Υ | Υ | N | N |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | N | N | N | N | N |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | N | N | N | N | N |
| Light hydrocracked distillate | 64741-77-1 | N | N | N | N | N |
| Mineral oil, white | 8042-47-5 | N | N | N | N | N |
| Naphthalene | 91-20-3 | Υ | Υ | Υ | N | Υ |
| Toluene | 108-88-3 | Υ | Υ | Υ | N | Υ |
| Benzene | 71-43-2 | Υ | Υ | Y | N | Υ |
| Ethylbenzene | 100-41-4 | Υ | Υ | Y | N | Y |
| Biphenyl | 92-52-4 | Υ | Υ | Υ | N | Υ |

Product identifier used on the label: MAG 1 TC-W3 2-CYCLE 6/1QT

Stock Number: MAG00609 Revision Date: 12-11-2020 Replaces: 07-14-2020

16. Other information, including date of preparation or last revision.

SDS Prepared by: DB_HAZOX
Revision Date: 12-11-2020

Revision Number: 55

Reason for revision: Activated by Document Formulation Generation

References:Other Info:
No data available
No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.