

SAFETY DATA SHEET

1. Identification

Product identifier	Sea Foam Spray		
Other means of identification			
Product code	SS14		
Recommended use	Engine treatment/cleaner.		
Recommended restrictions	Internal engine use only. Do not spray in atmosphere.		
Manufacturer/Importer/Supplier/Distributor information			
Company name	Sea Foam Sales Company		
Address	510 North Chestnut Street		
	Chaska, MN 55318		
	USA		
Telephone	(952) 938-4811		
Fax	(952) 938-5841		
Emergency telephone	INFOTRAC: (800) 535-5053 (Within Continental US); (352) 323-3500 (Outside US)		
	(Only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals)		

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	

denned nazarus

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage	Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures		010	0/
Chemical name		CAS number	%
Hydrocarbon blend		-	65 - 85
Isopropanol		67-63-0	10 - 20
Carbon dioxide		124-38-9	2 - 5
Composition comments	All concentrations are in percent by weight unl Chemical ingredient identity and/or concentrat present is confidential business information (tr 29 CFR 1910.1200(i).	ion information withheld for	
4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in center or doctor/physician if you feel unwell.	a position comfortable for b	eathing. Call a poisor
Skin contact	Remove contaminated clothing. Wash with ple medical advice/attention.	enty of soap and water. If sk	in irritation occurs: Ge
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Get		
Ingestion	Call a physician or poison control center imme vomiting occurs, keep head low so that stoma	ch content doesn't get into t	ne lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and trea Symptoms may be delayed.	at symptomatically. Keep vic	tim under observation
General information	Ensure that medical personnel are aware of th protect themselves. Show this safety data she		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemic	al powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this	s will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. Combustion products may include: carb oxides.		
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.		
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Fight fire from protected location or safe distance.		
Specific methods	Use standard firefighting procedures and cons containers from fire area if you can do so with		volved materials. Move
General fire hazards	Extremely flammable aerosol. Contents under exposed to heat or flame.	pressure. Pressurized conta	ainer may explode wh
6. Accidental release meas	sures		

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors/spray. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Move the aerosol cans to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas.
	Pick up undamaged aerosol cans mechanically. Dike leaked material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water. Collect runoff for recycling or disposal as potential hazardous waste.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. U.S. regulations require reporting releases of this material to the environment which exceed the reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. When using do not smoke. Protect containers from damage. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition.
	Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Avoid breathing mist/vapors/spray. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	PEL	5000 ppm	
Hydrocarbon blend	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
US. ACGIH Threshold Limit Values	5		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Hydrocarbon blend	TWA	5 mg/m3	Inhalable fraction.
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Тур	е	Va	lue	Form
	TWA	٩	900	00 mg/m3	
			50	00 ppm	
Hydrocarbon blend	Ceili	ing	180	00 mg/m3	
	STE	EL	10	mg/m3	Mist.
Isopropanol (CAS 67-63-0)	STE	EL	12	25 mg/m3	
			50	0 ppm	
	TWA	4	980	0 mg/m3	
			400	0 ppm	
iological limit values					
ACGIH Biological Exposure	e Indices				
Components	Value	Determinant	Specimen	Sampling T	Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*	
* - For sampling details, pleas	se see the source doo	cument			
	applicable, use pro	ilation should be us ocess enclosures, lo	cal exhaust venti	lation, or othe	r engineering controls to
dividual protection measures	applicable, use pro maintain airborne I established, mainta shower. , such as personal p	ilation should be us becess enclosures, lo levels below recomr ain airborne levels to protective equipme	cal exhaust venti nended exposure o an acceptable l ent	lation, or other limits. If expo evel. Provide e	r engineering controls to sure limits have not beer eyewash station and safe
dividual protection measures Eye/face protection	applicable, use pro maintain airborne I established, mainta shower. , such as personal p	ilation should be us ocess enclosures, lo levels below recomr ain airborne levels to	cal exhaust venti nended exposure o an acceptable l ent	lation, or other limits. If expo evel. Provide e	r engineering controls to sure limits have not beer eyewash station and safe
dividual protection measures	applicable, use pro maintain airborne l established, mainta shower. , such as personal p Wear safety glasse	ilation should be us ocess enclosures, lo levels below recomr ain airborne levels to protective equipme es with side shields	cal exhaust venti nended exposure o an acceptable l ent (or goggles). Fac	lation, or other e limits. If expo evel. Provide e e shield is rec	sure limits have not beer eyewash station and safe
dividual protection measures Eye/face protection Skin protection	applicable, use pro maintain airborne I established, mainta shower. , such as personal p Wear safety glasse Wear appropriate o	ilation should be us ocess enclosures, lo levels below recomr ain airborne levels to protective equipme es with side shields	cal exhaust venti nended exposure o an acceptable l ent (or goggles). Fac	lation, or other e limits. If expo evel. Provide e e shield is rec	r engineering controls to sure limits have not beer eyewash station and safe ommended.
dividual protection measures Eye/face protection Skin protection Hand protection	applicable, use pro maintain airborne I established, mainta shower. , such as personal p Wear safety glasse Wear appropriate o supplier.	ilation should be us ocess enclosures, lo levels below recomr ain airborne levels to protective equipme es with side shields	cal exhaust venti nended exposure o an acceptable l ent (or goggles). Fac loves. Suitable g	lation, or other e limits. If expo evel. Provide e e shield is rec	r engineering controls to sure limits have not beer eyewash station and safe ommended.
dividual protection measures Eye/face protection Skin protection Hand protection Skin protection	applicable, use pro maintain airborne I established, mainta shower. , such as personal p Wear safety glasse Wear appropriate o supplier. Wear appropriate o When workers are certified respirators	ilation should be us occess enclosures, lo levels below recomr ain airborne levels to protective equipme es with side shields chemical resistant g chemical resistant c facing concentratio s. Wear NIOSH app	cal exhaust venti nended exposure o an acceptable I ent (or goggles). Fac loves. Suitable g lothing. ns above the exp roved respirator a	lation, or other e limits. If expo evel. Provide e e shield is rec loves can be re posure limit the appropriate for	r engineering controls to sure limits have not beer eyewash station and safe ommended. ecommended by the glov
Skin protection Hand protection Skin protection Other	applicable, use promaintain airborne lestablished, maintain shower. , such as personal p Wear safety glasse Wear appropriate of supplier. Wear appropriate of When workers are certified respirators point of use. Appropriate	ilation should be us occess enclosures, lo levels below recomr ain airborne levels to protective equipme es with side shields chemical resistant g chemical resistant c facing concentratio s. Wear NIOSH app	cal exhaust venti nended exposure o an acceptable I ent (or goggles). Fac loves. Suitable g lothing. ns above the exp roved respirator a lection should be	lation, or other e limits. If expo evel. Provide e e shield is rec loves can be re posure limit the appropriate for made by a qu	r engineering controls to sure limits have not beer eyewash station and safe ommended. ecommended by the glov

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol spray can - Pressurized Liquid.
Color	Colorless.
Odor	Petroleum hydrocarbon.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	180 °F (82.2 °C)
Flash point	55.0 °F (12.8 °C) Tag Closed Cup
Evaporation rate	< 1
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits

Flammability limit - upper (%)	Not available.
Vapor pressure	80 - 90 psig
Vapor density	> 1 (Air=1)
Relative density	0.8
Solubility(ies)	
Solubility (water)	Slightly soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Heat of combustion	34 kJ/g
Oxidizing properties	Not oxidizing.
VOC	367 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Acids. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Prolonged inhalation may be harmful.	
Skin contact	Causes skin irritation.	
Eye contact	Causes serious eye irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.	

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.	
Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	12870 mg/kg
Inhalation		
Vapor		
LC50	Rat	72.6 mg/l, 4 hours
Oral		
LD50	Rat	4710 mg/kg
Skin corrosion/irritation	Causes skin irritation.	

Components	Species		Test Results
Ecotoxicity			s. However, this does not exclude the or damaging effect on the environment.
12. Ecological information			
Further information	Intentional misuse by concentrating and inhaling the product can be harmful or fatal.		
Chronic effects	Prolonged inhalation may be harmful.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Specific target organ toxicity - repeated exposure	Not classified.		
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.		
Reproductive toxicity	This product is not expected to ca	ause reproductive or dev	elopmental effects.
Not listed. OSHA Specifically Regulated Not regulated.	d Substances (29 CFR 1910.1001	-1053)	
NTP Report on Carcinogens			anogonaty to numerio.
IARC Monographs. Overall E Isopropanol (CAS 67-63-0	Evaluation of Carcinogenicity	Not classifiable as to car	cinogenicity to humans
Carcinogenicity	Not classifiable as to carcinogenicity to humans.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Respiratory sensitization	Not a respiratory sensitizer.		
Respiratory or skin sensitization	I		
Serious eye damage/eye irritation	Causes serious eye irritation.		

Components		Species	Test Results	
Isopropanol (CAS 67-63-0)				
Aquatic				
Acute				
Crustacea	LC50	Daphnia magna	> 10000 mg/l, 24 hours	
Fish	LC50	Pimephales promelas	9640 mg/l, 96 hours	
Chronic				
Crustacea	EC50	Daphnia magna	> 100 mg/l, 21 days	
	NOEC	Daphnia magna	141 mg/l, 16 days	
			30 mg/l, 21 days	
rsistence and degradability	No data is	available on the degradability of this pr	roduct.	
accumulative potential				
Partition coefficient n-octa Isopropanol (CAS 67-63-0)	nol / water (I	og Kow) 0.05		
bility in soil	The produ	The product is slightly soluble in water.		
ner adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.			
. Disposal consideratio	ons			
posal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.			

Local disposal regulationsDispose in accordance with all applicable regulations.Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste
disposal company.

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

-	
DOT	
UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	-
-	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Packing group	Not applicable.
Environmental hazards	-
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	-
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	
15. Regulatory information	
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Commun

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)
Isopropanol (CAS 67-63-0) Listed.
SARA 304 Emergency release notification
Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)
Not regulated.

Not listed.	dous substance			
SARA 311/312 Hazardous chemical	Yes			
Classified hazard categories	Gas under pressure Skin corrosion or irri Serious eye damage	itation		
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
Isopropanol		67-63-0	10 - 20	-
her federal regulations			10 20	
Clean Air Act (CAA) Section	n 112 Hazardous Air I	Pollutants (HAPs) List		
Not regulated.				
Clean Air Act (CAA) Section Not regulated.	n 112(r) Accidental Ro	elease Prevention (40 C	FR 68.130)	
Safe Drinking Water Act (SDWA)	Contains componen	t(s) regulated under the S	Safe Drinking Water Act.	
FEMA Priority Substan	ces Respiratory Heal	th and Safety in the Flav	or Manufacturing Work	place
Isopropanol (CAS 6	7-63-0)	Low priority		
state regulations				
US. Massachusetts RTK - S	Substance List			
Carbon dioxide (CAS 12 Hydrocarbon blend (CAS Isopropanol (CAS 67-63 US. New Jersey Worker and	S -) -0)	o-Know Act		
Carbon dioxide (CAS 12 Isopropanol (CAS 67-63- US. Pennsylvania Worker a	-0)	-to-Know Law		
Carbon dioxide (CAS 12 Isopropanol (CAS 67-63- US. Rhode Island RTK				
Carbon dioxide (CAS 12 Hydrocarbon blend (CAS Isopropanol (CAS 67-63	S -)			
	any chemicals currently	cement Act of 2016 (Prop / listed as carcinogens or /ov.		
•	• •		Regulations (Cal. Code	Regs, tit. 22, 69502.3,
Hydrocarbon blend Isopropanol (CAS 6	. ,			
ernational Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)
Australia	Australian Inventory	of Chemical Substances	(AICS)	Ye
Canada	Domestic Substance	es List (DSL)		Ye
Canada	Non-Domestic Subs	. ,		N
China		g Chemical Substances in		Ye
Europe	European Inventory Substances (EINEC	of Existing Commercial C	Chemical	Ye
	,	(0)		
Europe		tified Chemical Substance	es (ELINCS)	N
Europe Japan	European List of No			N Ye

Country(s) or region	Inventory name	On inventory (yes/no)*
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	09-November-2018
Revision date	-
Version #	01
HMIS® ratings	Health: 3 Flammability: 4 Physical hazard: 3
NFPA ratings	

Disclaimer

Sea Foam Sales Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.