Printing date 01/04/2023 Revised On 01/04/2023

#### 1 Identification of the substance and manufacturer

Trade name: **GREEN FLUORESCENT** 

0000200368 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:** 

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

## 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 







Signal word Danger

Extremely flammable aerosol. **Hazard statements** 

Contains gas under pressure; may explode if heated.

May damage fertility or the unborn child. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use.

**Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

Dangerous components:		
64742-89-8	VM&P Naphtha	15-25%
74-98-6		10-15%
106-97-8		5-10%
	Calcium Carbonate	5-10%
	Mineral Spirits	1-5%
1330-20-7	xylene (mix)	1-5%

#### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects: Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/04/2023 Revised On 01/04/2023

Trade name: GREEN FLUORESCENT

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

#### 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm (EX)

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm REL (USA) Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm BEI, A4

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use. Avoid contact with the skin.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

## 9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.

pH-value: Not determined.
Melting point/Melting range Undetermined.

Boiling point: -44 °C (-47.2 °F)

Flash point: -19 °C (-2.2 °F)

Flammability (solid, gas): Extremely flammable.

**Decomposition temperature:** Not determined.

**Auto igniting:** Product is not self-igniting.

**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % Vapor pressure: Not determined.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/04/2023 Revised On 01/04/2023

Trade name: GREEN FLUORESCENT

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined.

35.0 % Water:

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Not fully evaluated.

Chemical stability: Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

## 11 Toxicological information

LD/LC50 values that are relevant for classification:

1330-20-7 xylene (mix)

Oral LD50 8,700 mg/kg (rat) Dermal LD50 2,000 mg/kg (rbt) Inhalative LC50/4 h 6,350 mg/l (rat)

Information on toxicological effects: No data available.

Irritant to skin and mucous membranes. Skin effects:

Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. No further relevant information available. Other adverse effects:

# 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

**UN-Number** UN1950 DOT UN1950

DOT Aerosols, flammable **ADR** 1950 Aerosols

Transport hazard class(es):

Class 2.1 Gases Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group:

**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

#### 15 Regulatory information

#### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

## SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

**Toxic Substances Control Act** 

Canadian Domestic Substances List

(TSCA): All hazardous ingredients are found on the inventory list of substances.

All ingredients are listed or exempted. (DSL):

(Contd. on page 4)

# Safety Data Sheet

Printing date 01/04/2023 Revised On 01/04/2023

Trade name: GREEN FLUORESCENT				
Concumer Broduct Sefety	(Contd. of page 3)			
Consumer Product Safety Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.			
California Proposition 65 chemicals known to cause cancer:				
100-41-4 ethyl benzene				
Prop 65 chemicals known to cause birth defects or reproductive harm:				
108-88-3 Toluene				
EPA:				
1330-20-7   xylene (mix)				

# **16 Other information**

Contact: Regulatory Affairs